

ACRYLIC DISTEMPER.

Salient Features

- ❖ This Product is based on acrylic copolymer and specially designed to give elegant, smooth, durable and fungus free matt finish interiors.
- ❖ Relatively shorter recoatability period of 3 to 4 hrs enables the painter to finish job quickly.
- ❖ Its whiteness and color retention is excellent.

TECHNICAL DATA

Area Of Application	:	Interior plaster, brick work, asbestos, etc.
Method Of Application	:	Brush, roller or spray.
Consistency	:	300±10 units on penetrometer.
Finish	:	Smooth and matt.
Thinner Recommended	:	Potable water.
Drying (30°C and 60% r.h.)		
	Surface dry	: 10-15 minutes.
	Hard dry	: 3-4 Hrs
Primer Recommended	:	Godavari Universal Primer (Water thinnable or solvent thinnable)
Spreading Capacity	:	7±2 sq.mtrs/kg/coat depending upon the shade and surface(at recommended dilution i.e. paint 3: 2 water by wt)
Pack Size	:	2 Kg, 5 Kg, 10 Kg & 20 Kg.



DIRECTIONS FOR USE :

Surface preparation :

Give at least 6 months maturation time for new plaster. Ensure that the surface is free from dust, loose matter etc. prior to application previous coatings should be scrapped off if not in sound condition. Light sanding with emery paper no.320 is recommended for previous coatings in sound condition.

Application: Apply thin coat of Godavari Cement/Universal Primer (solvent/water based) if necessary. Apply wall putty in thin layers (Uno spray plaster) to overcome surface imperfections. One more coat of Godavari Cement/Universal primer is recommended as an undercoat on the putty for best results. Sand lightly with emery paper no. 320 and then apply 2-3 coats of Acrylic Distemper by brush or roller keeping as inter coat interval of 4-6 hours.

For touchup or self priming Godavari Cement Primer Water based and for new unpainted surface Godavari Cement/Universal Primer solvent based is recommended.

Do not over thin and strain thinned paint before application.

TECHNICAL AID SERVICE PROVIDED ON REQUEST

Mfd. by : **GODAVARI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Phone : 2372 3227, 2372 1249 Fax : 2377 5814

E-mail : admin@jayantcolor.com Website : www.jayantcolor.com

DEPOTS :

AHMEDABAD, BHIWANDI, NASIK, PUNE, VADODARA

C & F / AGENTS :

KOLHAPUR, COCHIN, DELHI, RAJKOT, VALSAD, BHUJ, KANPUR, JALANDHAR

Information in this leaflet is given in good faith but without warranty. Covering capacity indicated is under ideal conditions in the laboratory on proper prepared surfaces. Consumer is advised to verify the same practically at site as various conditions effects the parameters indicated above.