

## **GODAVARI SATIN FINISH**

### **SALIENT FEATURES :**

- ❖ The product which develops characteristic texture when rolled over has also excellent flow leveling drying and durability.
- ❖ Dust pick-up being minimum, the film is easy to clean and retains fresh look for longer period.

### **TECHNICAL DATA :**

<b>Areas of application</b>	:	Plaster, Wood, Metal and other such Interior surfaces.
<b>Method of Application</b>	:	Brush or Roller
<b>Viscosity</b>	:	120±10 sec. on Fordcup B4 at 30°C.
<b>Thinner recommended</b>	:	Godavari general purpose Thinner.
<b>Application Viscosity</b>	:	60±5 seconds on FCB4 at 30°C.
<b>Covering Capacity</b>	:	15±3 sq.mtr./Litre/coat depending upon the substrate and temperature.
<b>Drying (30°C and 60% r.h)</b>		
<b>Surface Dry</b>	:	Less than 3 hrs.
<b>Hard Dry</b>	:	Overnight.
<b>Finish</b>	:	Typical texture with Lustre.
<b>Flash Point</b>	:	> 30°C.

<b>TECHNICAL AID &amp; SERVICES PROVIDED ON REQUEST</b>
---

**Mfd By: GODAVARI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Compound, Darukhana, Reay Road, Mumbai 400010.  
Phone: 2372 3227, 2372 1249 Fax: 2377 5814

Email: admin@jayantcolor.com Website: admin@jayantcolor.com