

## "PEARL MAX " ACRYLIC LATEX PAINT

### Salient features:

- ❖ This product is an elastic, super protective & especially formulated for exterior walls. Due to its unique water resistant property and special paint preservatives it protects exterior walls from dampness, algae and fungus caused by lashing rain.

### TECHNICAL DATA

<b>Areas of application</b>	:	Masonry, Concrete, Brickwork, etc.
<b>Method of Application</b>	:	Brush, Roller
<b>Finish</b>	:	Smooth with slight sheen
<b>Thinner</b>	:	Potable Water
<b>Drying (30C and 60 ± 5% r.h)</b>	:	
<b>Surface Dry</b>	:	1 Hour
<b>Hard Dry</b>	:	4 to 6 Hours
<b>Spreading Capacity (at recommended thinning)</b>	:	On Normal Masonry surface by brushing : 5 6sq. mtrs../ltr/2 coats
<b>Recommended thinning</b>	:	35 to 45% by volume with water
<b>Recoating Interval</b>	:	4 to 6 Hours
<b>Packs Available</b>	:	1 Ltr., 4 Ltrs., 20 Ltrs.



## **DIRECTION FOR USE OF PEARL- MAX ACRYLIC LATEX PAINT :**

### **APPLICATION :**

Ensure that the plaster is completely dry, thoroughly clean and free from any grime, dust, flakes, grease, etc. Ensure that all water leakages/seepages are repaired before painting. For Old, prepainted surfaces, remove all loosely adhering particles, powdery material or defective paint by thorough brushing, scraping and water jetting, if required.

For areas severely affected by algae & fungus, application of **GODAVARI BIO WASH** is recommended.

Do not apply any kind of putty or primer. Surface imperfections such as holes, dents or cracks are to be filled with cement and sand mixture in the ration 1:3.

For best performance, it is recommended to apply one self priming coat of **PEARL MAX ACRYLIC LATEX PAINT** after diluting 1 litre of paint with 1 litre of water, for any kind of surface or **COLORSOL** polymer Primer.

### **HEALTH & SAFETY**

Store container in upright position, with lid tightly closed, in a cool, dry place.

Keep out of reach of children and away from food, drink and animal feed. May be harmful if swallowed.

In case of ingestion seek immediate medical attention.

Ensure good ventilation at all times. Do not breathe vapour or spray. Avoid inhalation of dust by wearing a suitable nose pad during sanding and surface preparation.

Wear eye protection during application. In case of contact with eyes, rinse immediately rinse plenty of water and seek medical advice.

Remove splashes from skin with soap and water or a recognized skin cleanser.

Do not pour left over paint down drains or in water courses. Curtail spillage using sand or earth.

## **TECHNICAL AID SERVICE PROVIDED ON REQUEST**

Mfd. by : **GODAVARI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Phone : 2372 3227, 2372 1249 Fax : 2377 5814

E-mail : [admin@jayantcolor.com](mailto:admin@jayantcolor.com) Website : [www.jayantcolor.com](http://www.jayantcolor.com)

### **DEPOTS :**

AHMEDABAD, BHIWANDI, NASIK, PUNE, VADODARA

### **C & F / AGENTS :**

KOLHAPUR, COCHIN, DELHI, RAJKOT, VALSAD, BHUJ, KANPUR, JALANDHAR

Information in this leaflet is given in good faith but without warranty. Covering capacity indicated is under ideal conditions in the laboratory on proper prepared surfaces. Consumer is advised to verify the same practically at site as various conditions effects the parameters indicated above.