

**"PEARL ULTIMA " ( D. P. R. )**  
**Advanced Anti-Algal Weather Proof Paint**

**Salient features:**

- ❖ This product is a water-based, modified acrylic, anti algae, high performance exterior wall finish & has minimum dust pick-up.

**TECHNICAL DATA**

<b>Areas of application</b>	:	It can be applied on various types of exterior cement plasters, asbestos sheets, concrete structures and Mangalore Tiles. This Product cannot be applied on surfaces / substrates that are subjected to continuous seepage or dampness.
<b>Method of Application</b>	:	Brush, Roller or Spray
<b>Finish</b>	:	Smooth with slight sheen
<b>Thinner</b>	:	Potable Water
<b>Drying (30C and 60 ± 5% r.h)</b>		
<b>Surface Dry</b>	:	30 Minutes
<b>Hard Dry</b>	:	4 to 6 Hours
<b>Spreading Capacity (at recommended thinning)</b>	:	On Normal Masonary surface by brushing : 5 - 6 sq.mtrs / litre / 2 coats
<b>Recommended thinning</b>	:	35 to 45% by volume with water
<b>Recoating Interval</b>	:	4 to 6 Hours
<b>Packs Available</b>	:	1 Ltr., 4 Ltrs., 20 Ltrs.



## **DIRECTION FOR USE OF PEARL - ULTIMA Advanced Anti-Algal Weather Proof Paint :**

### **APPLICATION :**

Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water

Application of any kind of putty is not recommended. Surface imperfections such as holes, dents, cracks are to be filled only by using mixture of white cement & fine sand (in the ratio of 1:3).

Freshly plastered surfaces must be allowed to cure completely.

### **PERFORMANCE FEATURES & BENEFITS**

It provides long lasting exterior performance even in the most extreme tropical conditions of India.

Its unique anti algae chemistry ensures that exterior walls are provided with power packed resistance against algae and fungi growth.

It has very good dirt pick up resistance and dirt cleaning properties.

### **PRECAUTIONS :**

Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.

Do not apply when relative humidity is more than 85%.

Do not over-thin or over-extend the brush.

Do not use any Universal Stainers or any other Colorants.

Ensure that horizontal surfaces like top of windows, ledges and other horizontal surfaces, etc. are painted with 3 coats for greater protection.

Stir well and strain before use.

Tinted paints need thorough shaking immediately after tinter addition as well as before use.

### **POST APPLICATION INSTRUCTIONS**

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

**TECHNICAL AID SERVICE PROVIDED ON REQUEST**

Mfd. by : **GODAVARI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Phone : 2372 3227, 2372 1249 Fax : 2377 5814

E-mail : admin@jayantcolor.com Website : www.jayantcolor.com

### **DEPOTS :**

AHMEDABAD, BHIWANDI, NASIK, PUNE, VADODARA

### **C & F / AGENTS :**

KOLHAPUR, COCHIN, DELHI, RAJKOT, VALSAD, BHUJ, KANPUR, JALANDHAR

Information in this leaflet is given in good faith but without warranty. Covering capacity indicated is under ideal conditions in the laboratory on proper prepared surfaces. Consumer is advised to verify the same practically at site as various conditions effects the parameters indicated above.