

"Smooth Emulsion Paint" For Interiors

Salient features:

- ❖ This product offers optimum performance, with respect to protection and decoration of interior walls.
- ❖ It is formulated by using an ideal combination of pigments and extenders, dispersed in a co-polymer emulsion for a smooth and pleasant matt finish.

TECHNICAL DATA

Areas of application	:	Interior Walls, Ceilings, Plaster, Bricks, Asbestos, etc.
Method of Application	:	Brush or Roller
Finish	:	Smooth & Matt
Thinner	:	Potable water
Drying (30C and 60 ± 5% r.h)	:	
Surface Dry	:	minimum 30 Minutes.
Hard Dry	:	minimum 5 Hours.
Spreading Capacity (at recommended thinning)	:	19 - 20 sq.mtrs./ltr./ 1 coat (On a smooth non-absorbent surfaces)
Recommended thinning	:	50 to 60% by volume with water
Recoating Interval	:	5 to 6 Hours
Packs Available	:	1 Ltr., 4 Ltrs., 20 Ltrs.



DIRECTION FOR USE OF SMOOTH EMULSION PAINT :

Surface preparation :

Ensure the surface is clean, dry and free from all defective or poorly adhering material, dirt, grease, wax, etc. Remove all loose or poorly adhering materials by rubbing down, using a suitable abrasive paper and thereafter wipe off. Apply a coat of GODAVARI Cement Primer (Water / Solvent base) followed by Putty to level the dents and make the surface uniform. Apply a coat of GODAVARI Cement Primer (Water / Solvent base) again. Then apply two to three coats of Godavari Smooth Emulsion Paint

Application :

Dilute the paint as per recommended dilution and apply 2 or 3 coats at an interval of 5 to 6 hours.

TECHNICAL AID SERVICE PROVIDED ON REQUEST

Mfd. by : **GODAVARI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Phone : 2372 3227, 2372 1249 Fax : 2377 5814

E-mail : admin@jayantcolor.com Website : www.jayantcolor.com

DEPOTS :

AHMEDABAD, BHIWANDI, NASIK, PUNE, VADODARA

C & F / AGENTS :

KOLHAPUR, COCHIN, DELHI, RAJKOT, VALSAD, BHUJ, KANPUR, JALANDHAR

Information in this leaflet is given in good faith but without warranty. Covering capacity indicated is under ideal conditions in the laboratory on proper prepared surfaces. Consumer is advised to verify the same practically at site as various conditions effects the parameters indicated above.