

## **WETCHECK**

Invisible Protector of Masonry

### **What is WETCHECK ?**

**WETCHECK** is a ready-to use - colourless impregnating liquid coating with deep penetrating property, to be used on exteriors of buildings.

### **Properties**

**WETCHECK** is a ready-to use - colourless impregnating liquid coating with deep penetrating property, to be used on exteriors of buildings.

**WETCHECK** : is water-based with no solvents, possessing deep penetrating effect produced in ready-to-use consistency.

Offers maximum protection to surfaces against heavy rains or moisture and penetration of water.

Does not effect the original breathing capacity of concrete, bricks and masonry as it does not seal surface pores.

### **Advantages**

**WETCHECK** : Serves as an excellent waterproofing and damp proofing agent as it protects the exterior masonry efficiently against penetration of moisture to interiors.

Keeps the interiors dry during all seasons.

Prevents damage to masonry exposed to severe atmospheric conditions.

Does not affect the breathing capacity of impregnated surfaces.

Prevents efflorescence and reduces moss and fungus growth.

Serves as an effective shield against dust and soot.

Possesses good penetration capacity on low absorption and also on moist surfaces.

Provides long and durable water repellency to buildings due to its water repelling properties.

Does not change the colour or nature of the impregnated portions. Is effective 1-2 hours after application.

### **Where to apply**

WETCHECK can be applied on almost all kinds of surfaces having slight absorption properties like :

Bricks  
Fair faced Concrete  
Light Concrete  
All types of plasters

Cylinder Tiles  
Clinkers  
Renderings  
Cast Stones

It is suggested that a preliminary trial carried out while impregnating any nonabsorbent surface to check the effect of the application or where there is strong dusting on the surface during application or when the coating is wet.



## **Surface Preparation**

The surface should be dry and free from contamination. The plaster should be at least 2 weeks old. Also, cracks if any should be property filled and other surface defects rectified before applying WETCHECK. WETCHECK is to be applied on exterior only.

## **Application**

WETCHECK can be applied by any brush or spraying. One coat with sufficient material per application will do to get good impregnation. On highly absorbant surfaces two coats are recommended.

## **Coverage**

Depends on the nature of the surface and also its capacity to absorb. WETCHECK normally covers approx 100 - 150 sq. ft. per litre.

**Packing** : 20 Litre Drums, 5 Litre Cans.

**NOTE** : The above information and details are based on the test conducted and experience on application and usage. The user is advised to carry out tests and take trials to satisfy himself on the suitability of the product meeting his requirement considering prevailing conditions prior to applying/using the product on larger area. As the conditions under which the products are used or transported are beyond our control, we will not hold ourselves responsible for its consequential performance.

## **TECHNICAL AID SERVICE PROVIDED ON REQUEST**

Mfd. by : **JAYANT COLOR & CHEMICAL INDUSTRIES**  
Tulsiram Gupta Mills Estate, Darukhana, Reay Road,  
Mumbai - 400 010. Phone : 2372 1249, 2379 0135 Fax : 2377 5814  
E-mail : [admin@jayantcolor.com](mailto:admin@jayantcolor.com) Website : [www.jayantcolor.com](http://www.jayantcolor.com)

### **BRANCHES/DEPOTS :**

AHMEDABAD /BHIWANDI/NASIK/PUNE/VADODRA

### **C&F/AGENTS :**

BHUJ/ COCHIN/DELHI/JALANDHAR / KANPUR / KOLHAPUR / RAJKOT/ VALSAD